



GYA553 setting




By connecting the T16IZ(S) and the 6-axis gyro GYA553 for airplanes, you can set the GYA553.

Connection T16IZ(S) and GYA553


T16IZ(S)



Receiver Connection Cable
(included with gyro)



GYA553



⚠ CAUTION

❗ Be sure to connect and disconnect the GYA553 and T16IZ(S) connection cable with the power off.

Gyro setting GYA553



1	Model menu	Model 1 Normal	7.8V	1/1
	Servo monitor	Condition select	AFR	
	Dual rate	Program, mixes	Sequencer	
	Pitch curve	Throttle curve	Acceleration	
	Throttle hold	Swash mixing	Throttle mixing	
	Pitch → Needle	Pitch → Rudder	Gyro	
	Governor	Gyro Setting		

1. Select "Gyro setting" on the last page of Airplane Model Menu



2. Select "Start"

When "GY Settings Transfer" is selected, the gyro setting data saved in T16IZ(S) is written to the gyro.



Select "Start"
This will download the gyro data to the T16IZ(S).

3	GYA553	Airplane Condit.1	7.4V
	Holding Power	C5	6.4V
	AIL Gyro	OFF	Basic Menu
	ELE Gyro	OFF	
	RUD Gyro	OFF	
	Gyro Version	2.0	


To Basic menu

3. Home screen is displayed

◆ When copying data from Gyro A to Gyro B



Connect the gyro A to the T16IZ(S) and press [Start]. (Enter the data of A into T16IZ(S))



If you press Start here, the B data will be download to the T16IZ(S) and the A data will be lost.

Connect Gyro B to T16IZ(S) and press [GY Settings Transfer]. (Put data on A into gyro B)

Home screen

On the home screen, basic information such as gyro operation mode, sensitivity, battery voltage are displayed.

Gyro operation mode / Gyro gain

Displays "AVCS" or "Normal" operation mode and gyro gain of aileron (roll), elevator (pitch) and rudder (yaw) axis.

GYA553 Software version

The software version of the connected GYA553 is displayed.

The Home screen displays the following information:

- GYA553 Airplane Condit. 1
- Battery voltage: 7.4V
- Holding Power: C5
- AIL Gyro OFF
- ELE Gyro OFF
- RUD Gyro OFF
- Gyro Version: 2.0

A callout box labeled "Battery voltage" points to the 6.4V reading, stating: "Displays the voltage of the receiver battery connected to GYA."

Basic menu

Home screen

The Home screen displays the following information:

- GYA553 Airplane Condit. 1
- Battery voltage: 7.4V
- Holding Power: C5
- AIL Gyro OFF
- ELE Gyro OFF
- RUD Gyro OFF
- Gyro Version: 2.0

The "Basic Menu" button is highlighted with a blue box.

Basic menu

The Basic menu displays the following information:

- Basic Menu Airplane Condit. 1
- Battery voltage: 7.8V

The "Config" and "SBus Basic" options are highlighted with green boxes.

◆ Config

The Config menu displays the following information:

- Config Model1 Condit. 1
- Battery voltage: 7.6V
- Gyro Set Dir: Up, Left, Down, Right
- Wing: Normal, ELEVON
- Tail: Normal, V-Tail
- Servo Type: DG:285Hz, AN: 70Hz
- SB/R2 Out: SBus(HS), RUD2, Ch3(Thr), SBus(Std)

◆ S.BUS basic

The S.BUS basic menu displays the following information:


- SBus Basic Model1 Condit. 1
- Battery voltage: 7.6V
- AIL: CH1, Gain AIL, CH5
- ELE: CH2, Gain ELE, CH7
- RUD: CH4, Gain RUD, CH8
- AIL2: INH, ELE2, INH
- RUD2: INH, RUD2, INH

Config

Config 1/9 Gyro set mounting direction

Config	Model1	Condit.1	7.6V	1/9
Gyro Set Dir	Up	Left	Down	Right
Wing	Normal	ELEVON		
Tail	Normal	V-Tail		
Servo Type	DG:285Hz	AN:70Hz		
SB/R2 Out	SBus(HS)	RUD2	Ch3(Thr)	SBus(Std)

Set the mounting direction of GYA. Set mounting direction with reference to figure below.




Config 1/9 WING/TAIL


Set with the wing type/tail type of GYA553. The wing type/tail type of the transmitter is not used and is normal.

- Turn off the elevon/V-tail mixing on the transmitter side.
- Do not use transmitter sub-trim. Adjust using the gyro neutral offset.
- When using the S.BUS servo, you can also use the neutral offset function of the S.BUS servo setting parameters.

Config	Model1	Condit.1	7.6V	1/9
Gyro Set Dir	Up	Left	Down	Right
Wing	Normal	ELEVON		
Tail	Normal	V-Tail		
Servo Type	DG:285Hz	AN:70Hz		
SB/R2 Out	SBus(HS)	RUD2	Ch3(Thr)	SBus(Std)



Select wing type




Select tail type



Gyro setting GYA553

Config

Config 1/9 Servo type



Digital servo

Analog servo

Select the servo type according to the servo to be used.

Digital servo → DG : 285 Hz

Analog servo → AN : 70 Hz

The stability of digital-servo mode of a flight increases in order to perform a high-speed control action.

Config 1/9 SB/R2 OUT



Select the SB/R2 port.

S.BUS


Rudder 2

Throttle

S.BUS devices can be connected to this port.



When using two rudder servos



Config


Config 2/9 Gyro direction

It is the direction setting of the gyro. Be careful as it will crash if the direction is reversed.


For dual aileron, dual elevator, and dual rudder aircraft, check the operating direction of each second aileron/elevator/rudder.

Config		Model1	Condit.1		7.6V	2/9
Gyro Dir						
AIL	Normal	AIL2	Normal			
ELE	Normal	ELE2	Normal			
RUD	Normal	RUD2	Normal			
AIL3	Normal	AIL4	Normal			


Tilt the airplane to the left on the ground and check that the ailerons operate to the right.



Turn the airplane to the right on the ground and check that the rudder operates to the left.







Raise the airplane with its nose upward and check that the elevator operates downward.



Config 3/9 Neutral offset

Config		Model1	Condit.1		7.6V	3/9
Neutral Offset						
AIL	+0	AIL2	+0			
ELE	+0	ELE2	+0			
RUD	+0	RUD2	+0			
AIL3	+0	AIL4	+0			

Neutral position setting for each servo.



This will move the neutral to the desired position.

Config


Config 4/9 5/9 Servo limit

Config	Model1 Condit.1	7.6V	4/9
Srv.Limit			
AIL	100 %	100 %	
ELE	100 %	100 %	
RUD	100 %	100 %	
AIL3	100 %	100 %	


This is the limit setting for each servo. The position of the maximum operation is read into the gyro in the first setting.

Config	Model1 Condit.1	7.6V	5/9
Srv.Limit			
AIL2	100 %	100 %	
ELE2	100 %	100 %	
RUD2	100 %	100 %	
AIL4	100 %	100 %	

Aileron example




Stick to full right



Adjust the value (%) to reach the maximum operating position



Stick to full left



Adjust the value (%) to reach the maximum operating position

Config

Config 6/9 Holding Power

It is a function to adjust the posture holding force of the aircraft in AVCS mode. Decreasing the value weakens the holding power and makes the operation feeling closer to the normal mode.

The current rate numbers C1 to C5 are displayed by operating the channel of the transmitter.

Like the flight condition function of the transmitter, you can set up to 5 different data for the attitude holding force rate of the aircraft in AVCS mode by operating the switch from the transmitter, and switch between them. You can set the holding power rate selector switch to the channel with the AFR function of the transmitter, and set the point for each rate on the AFR point curve to switch. It is also possible to use the flight condition function to work with the flight condition switch.

Config 6/9

Holding Power C3 / BK

AIL	100	C3
ELE	100	C3
RUD	100	C3

With the switch button, the "holding power" of each rate (C1 to C5) can be displayed and adjusted.

S.BUS Basic 2/4

Holding Power CH12

C3 / BK

-100 0 100

C2 P2

C3 P3


C4 P4

C5 P5


By operating the channel of the transmitter, the channel position of the current rate numbers C1 to C5 will be displayed in green.

Display and adjust the current rate numbers C1 to C5 by operating the channel on the transmitter.

When set to SW of DG1 or DG2



When set to dial or lever



Config

Config 7/9 4D Flight (Backward flight) Gyro Reverse Mode Adjustment

Page 7 is for setting the gyro reverse mode. This is a special setting for 4D backward flight. Select whether to reverse the control direction of the aileron, elevator, and rudder when flying backward. Normally, when flying backward, the steering direction of all the rudder is reversed, so the control direction of the gyro is also reversed.

Switching between forward (FW) and reverse (BK) uses the same CH12 signal as the holding force. Up from near the midpoint of the throttle stick is forward, and down is reverse.


For details on setting the switching point, please refer to the transmitter settings.

In gyro reverse mode, the gyro controls in the same direction as the aircraft's tilt. Switch between forward and reverse to check that the gyro control direction changes correctly.

Config 7/9



S.BUS Basic 3/4



Config 8/9 4D Flight (Backward flight) Mode Adjustment

Page 8 is for setting the gyro reverse mode. This is a special setting for 4D backward flight.

The AET (BK) and AET (FW) functions estimate the aircraft's flight attitude during forward and backward transitions and optimize gyro control. If the aircraft's attitude changes quickly, decrease the value. If the attitude changes slowly, increase the value. The correction values for forward and backward transitions can be set independently. The setting range is 0 to 30. The OPC parameter adjusts the speed when the control amount increases and decreases. The setting range is 0 to 27. The values in the setting example are the standard setting values for SkyLeaf-ST. The optimal value will vary depending on the aircraft characteristics and flight style.



Config 9/9 Reset



Reset each Config item. It returns to the initial value.

Gyro setting GYA553


SBUS Basic menu

Set the CH for each function according to the transmitter to be used. Any unused functions should be set to INH (Inhibited).



The channel of each function can be changed.


Tap to move to the rate switching CH setting page.






Holding Power C2 to C5

⚠ WARNING

① Always verify that the S.BUS function assignments match your transmitter's function (in the FUNCTION menu) assignments. If any changes are made within the transmitter function assignments, then it will also be necessary to make the changes within the S.BUS function assignments. To change the channel, GYA553 and T16IZ(S) must be connected.



Tap the CH used for rate switching to select it.



ON-OFF channel for auto recovery

Reset each S.BUS function. It returns to the initial value.

